



www.gmspano.com

GMS Pano Elektrik San. Tic. A.Ş.

Beylikdüzü O.S.B. Bakır Ve Piring
Sanayi Sit. Leylak Cad. No:4
Beylikdüzü/İSTANBUL

+90 212 875 73 15
info@gmspano.com

DT4000

MODULER MODEL

CHARACTERISTICS

Material

ZA Galvanized Sheet, long service life against corrosion

Surface

Anti-corrosion coating, epoxy-polyester polymerized electrostatic powder coating

COLOR RAL 7035 Ragged

Busvar Brackets:

IEC 60695-2-11: 960° 30s / 30s all plastic parts are resistant to heat rises and fire caused by electrical effects, as specified in bearings for live metal surfaces.

Electrical Characteristics of the Panel

✓ In accordance with IEC 61439-1/2.

✓ In accordance with IEC 61641:2014.

Nominal isolation voltage for main bus: 1000V

Nominal current :4000A(Call us for 5000A applications.)

Peak value of withstand current Ipk: 220kA

Peak value of short-term withstand current Icw:100kA rms/1sn

Frequency: 50/60 Hz

FUNCTIONAL SYSTEM

- IP 20-30-31-54-55-65
- IK 08,10
- Detachable structure
- Its depth can be increased by adding side-by-side or back-to-back.
- Width in main body ;
500-600-700-900 and 1100 mm can create 300-400 mm or 500 mm channels in itself.
- Additional channel width ;
- 300-400 veya 500 mm
- Depth:
400-1000 mm
- Height:
1500-2200 mm
- Optional flat or transparent door



www.gmspano.com